

Shuttle Bus PMC

The Shuttle Bus PMC is an intelligent interface card providing all Launch Data Bus, Ground Data Bus, Multiplex De-Multiplex Multiple Remote Terminal, and Ground Data Bus (GDB) capability to the Shuttle Bus, together with a Pulse Code Modulation Mode. This card provides all features and functions required in a PMC platform, with Simplex & Half-Duplex modes provided. Specific operational modes provided include for LDB_BCT, LDB_MRT, GDB_BCT, GDB_MRT, BUS_MON, MDM_MRT, Primitive and Calibration modes.

SPECIFICATIONS

General Specifications

- Meets requirements of NASA spec. **84K08050**.
- LDB_BCT Mode and LDB_MRT Mode
- GDB_BCT Mode and GDB_MRT Mode
- Bus Monitor Mode
- MDM_MRT Mode
- Pulse Code Modulation Mode
- BIT and diagnostics
- IRIG-B timing 64 bit
- Programmable TX amplitude
- Full error injection and detection

Launch Data Bus, Bus Controller Terminal

Programmable message structure
Programmable IRQ Control register
Programmable Command word
Programmable TX error word & word number
Programmable data buffers
Programmable data word-count and direction
Message event register
Bit pattern register
Bit mask register
Programmable gap time
Time stamping, 64 bit, resolution 0.5 usec
Messages and data changeable in real time

Launch Data Bus, Multiple Remote Terminal

Full simulation/monitoring of single RT
If disabled, actual Shuttle Bus RT activity captured
Comprehensive RT simulation table provided, includes:
RT Mode, RT state machine register, IRQ control,
TX/RX data buffers, Primary/Secondary last command
time/value and state machine update, Go-Ahead,
Interrogate with no GPC data, Interrogate with GPC
data available, Status request, and FRC TX error
injection definition

Ground Data Bus, Bus Controller Mode

Measurement Poll tables, with addressing information
Command Queues
Uplink/Downlink queue
Passive/Active Monitor Mode, selectable by mode word
Passive/Active mode selectable dynamically

Ground Data Bus, Multiple Remote Terminal

Simulation/monitoring of all 256 RT's
Global definition for each RT
Defined in MRT Simulation table
40 bit mode intermediate look-up-table
Channel look-up-table, supporting Command,
Discrete, Measurement and Analog modes.

Bus Monitor Mode

Provides full capture and storage of all Shuttle-bus
activity, in both LDB and GDB modes.
Programmable triggers, includes Bus Definition, Bit
pattern, Bit mask, and error event,
Programmable post-trigger count, & stack start/end.

MDM-MRT Mode

Simulation of all 32 Remote Terminals
Enhanced MDM capability.
Local and Actual PROM support
Full error injection
HI/LO priority message queues

PCM Modes supported

NRZL, Bi-Phase-L
Bi-Phase-M, Bi-Phase-S

Host Interface

PCI: Slave, 32 Bit data
Memory Space: 2 Mbytes

Power

+5v +/- 5% 900 mAmps
+12V +/- 5% 50 mAmps

Environmental

Operating Temp. 0 – 50°C
Storage Temp. -20 – 70°C
Humidity 5% – 95% Noncondensing
MTBF (MIL 217F) 126,186 hrs at 25°C (Gb).

Order Codes

1U10980G01 IIB-SB-PMC

Contact Information

Technical & Sales queries: support@western-av.com
Phone: 353-61-472233
Fax: 353-61-471675
Web-site: <http://www.western-av.com>